

Venetian Blind Zigbee Motor User Manual



Models & Parameters (more info please refer to the nameplate)






03 Power Options

Adapter





04 Caution!

1. This product is for indoor use only, do not use outdoor or in humid environments. 2.Power supply: adapter 12V/2A,power box 12V/1A.

3. The motor will jog in operation, please do not proceed to the next step until it complete. 4.During operation, the effective interval of the transmitter button operation is 10 seconds. If there is no effective transmitter operation for more than 10 seconds, it will automatically exit the current mode.

5.The motor can be paired with max 10 controllers.

6.Upper&Lower limits cannot be set at the same position, limits saved even power off.

7. The motor runs constantly for at 6 mins max without any other operation.

8.Do not lift the motor by grabbing and pulling the power wire or the antenna.




Pairing Button functions


Functions	Operation	Jogging time	Note
Control the UP/STOP/ DOWN of the shade	Short press	/	It should be used when limits being set
Adding/Removing Controller	Hold for 2s	Jog*1	Operation needs be done within 10s
RF Control Inactive	Hold for 6s	Jog*2	Hold Pairing button for 6s, jog twice to show the motor RF control is inactive; Hold Pairing button for 2s, the RF control is active again.
Direction Reverse	Hold for 10s	Jog*3	All settings saved after direction reversed
Reset	Hold for 16s	Jog*4	All settings deleted

a.Pairing Motor with Controll

Way 1: Before adding a new controller



Way 2: After motor is powered on for more than 10s



Way 3:Power on,add controller B via pre-existing controller A





▲


Note: Pairing can not be done under group channel or 0 channel.

Jog x2






If the limits are not set, and direction goes opposite.




If limits are set and direction goes opposite.







Note: Do reverse the direction when it goes opposite.














Note: Upper&Lower limits cannot be set at the same point.

Before limits set, the motor will run in one-touch mode by pressing Up or Down, hold Up or Down for 2s, motor runs in constant-touch mode.

Once limits set, press Up or Down, motor runs in constant-touch mode.


Same operation can toggle from one-touch to constant -touch mode.

Note: When motor in one-touch mode, hold Up or Down for more than 2s, it will run in constant-touch mode.


fast get to the Fav. point

Note: The Fav.position setting only can be done after upper&lower limits set.

g.Adjusting Upper & Lower Limits



Note: The operation should be done within 4mins.



Speed decrease

Note: If motor doesn't jog, the max/min speed has already been reached. There are 3 speeds adjustable.



Remove a single controller



Remove controller B via pre-existing controller A




Controller B removed

Remove all controllers:



All controllers removed

Note: All the settings are saved even controllers removed(limits set are saved). Controller A/B are already paired to motor.



Limits cancelled

Note: It is forbidden to run the motor if installed into the shade without limits. Limits should be set immediately to protect the shade.

06 Installation & Connecting to external Zigbee module network



*Connection requirement

a.Make sure the phone is connected to the Wi-Fi network

b.The Tuya Zigbee gateway device needs to be added to the "Smart Life" APP firstly, please refer to its manual for details.

1 Download APP

a. Search "Smart Life" in the app store or scan the QR code

b.Complete account registration and login to the app



• Working voltage: 3V~3.6V

Certification: CE, FCC

For Indoor Use only


Supporting protocol: 802.11B/G/N20

• Working Temperature: −10°C~55°C

Smart Life



a. Power on, insert Zigbee module to motor module connection wire



b. Wait for 10s to see if the indicator is blinking




c. If indicator didn't blink, pls try: Method 1: Long insert RESET button until indicator blinking, motor's ready to Zigbee connection




Note: You can try Method 2 if it is not easy to insert RESET on module

Method 2: Short Press Prg on back of controller, motor jogs once; short press Down, motor jogs once, then short press UP, motor jogs once and blue indicator blinks which means motor enters Zigbee connection status.




d.Find the added Tuya Zigbee gateway on the "Smart Life" App, click "+" to add a subdevice, and then click "LED already blink", the APP will automatically search for motor device





direction



Smart Roller Shade Contra Device added successful Add subdevice



Search devic

Done





f. The Zigbee module indicator is always on after successful network connection.

Master Roller Shade Master Roller Shade 49% Opening 11 ~ ÷ : •

g.Enter the main interface to control the operation of the venetian blind.

